



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT



SEP 22 2014

Mr. Robert Boston
Berry Petroleum Company
5201 Truxtun Avenue, Suite 100
Bakersfield, CA 93309

Re: Notice of Minor Title V Permit Modification
District Facility # S-1246
Project # S-1124102

Dear Mr. Boston:


Enclosed is the District's analysis of your application for minor Title V permit modification for the facility identified above. You proposed a Title V minor permit modification to incorporate recently issued Authorities to Construct S-1246-334-3, 370-2, 370-3, 372-0, 373-0 and 374-0 into the Title V operating permit. The modifications include installing three new tanks connected to vapor recovery systems.

Enclosed is the engineering evaluation with the following attachments: proposed modified Title V permit, recently issued Authorities to Construct S-1246-334-3, 370-2, 370-3, 372-0, 373-0 and 374-0, emission increases, application, and previous Title V permit. This project will be subject to a 45-day EPA commenting period prior to the District taking final action.

If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Thank you for your cooperation in this matter.

Sincerely,


Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Gerardo C. Rios, EPA (w/enclosure) via email

Sayed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

TITLE V APPLICATION REVIEW

Minor Modification
Project #: S-1124102

Engineer: Steve Roeder
Date: 9/10/14

Facility Number: S-1246
Facility Name: Berry Petroleum Company
Mailing Address: 5201 Truxtun Avenue, Suite 100
Bakersfield, CA 93309

Reviewed by AP SUPER ADE

SEP 18 2014

Contact Name: Robert Boston
Phone: (661) 616-3808

Responsible Official: Robert Boston
Title: Manager of EHS

I. PROPOSAL

Berry Petroleum Company is proposing a Title V minor permit modification to incorporate the recently issued Authorities to Construct S-1246-334-3, 370-2, 370-3, 372-0, 373-0 and 374-0 into the Title V operating permit. The modifications include installing three new tanks connected to vapor recovery systems.

The purpose of this evaluation is to identify all applicable requirements, determine if the facility will comply with the applicable requirements and to provide the legal and factual basis for the proposed revisions.

II. FACILITY LOCATION

The new tanks are located at the 21Z lease and the Fairfield Water Plant (Section 20, Township 30S, Range 22E) in Berry Petroleum's Heavy Oil Western Stationary Source.

III. EQUIPMENT DESCRIPTION

- S-1246-334-4: 20,000 BBL FIXED ROOF TANK WITH VAPOR CONTROL SYSTEM, INCLUDING OPTIONAL COMPRESSOR, SHARED WITH S-1246-335, -336 AND -374, WITH VAPOR PIPING CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1246-152 (FAIRFIELD A-1 WATER PLANT)
- S-1246-370-4: 30,000 BBL TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179 ALSO SERVING TANK -372
- S-1246-370-5: 30,000 BBL TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179 ALSO SERVING TANKS -372 AND -373
- S-1246-372-1: 5,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-370 (21Z LEASE)
- S-1246-373-1: 5,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-370 (21Z LEASE)
- S-1246-374-1: 28,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-334 (FAIRFIELD WATER PLANT)

IV. SCOPE OF EPA AND PUBLIC REVIEW

This change to a Title V permit is considered to be a minor modification and, as such, requires no public review.

V. APPLICABLE REQUIREMENTS

District Rule 2520, Federally Mandated Operating Permits (Adopted June 21, 2001)

VI. DESCRIPTION OF PROPOSED MODIFICATIONS

Berry Petroleum has built three new oil tanks (S-1246-372, -373 and -374) and connected them to the vapor recovery systems listed on tank permits S-1246-334 and -370.

S-1246-334-4

The equipment description has been revised to include tank -374 on its vapor piping as listed above. There are no changes to the permit conditions.

S-1246-370-4

The equipment description has been revised to include tank -372, as indicated above. This permit will not be issued as it will be immediately replaced with -370-5.

The following condition has also been added to the permit:

1. Total VOC emissions from the components associated with tank up to vapor control system trunk line and tank piping to vapor control system S-1246-179 shall not exceed 71.6 lb/day. [District Rule 2201]

There are no other changes.

S-1246-370-5

The equipment description has been revised to include tanks -372 and -373, as indicated above.

The following condition will be carried from -370-4:

1. Total VOC emissions from the components associated with tank up to vapor control system trunk line and tank piping to vapor control system S-1246-179 shall not exceed 71.6 lb/day. [District Rule 2201]

There are no other changes.

S-1246-372-1

This is a new oil tank, therefore there are no changes.

S-1246-373-1

This is a new oil tank, therefore there are no changes.

S-1246-374-1

This is a new oil tank, therefore there are no changes.

VII. COMPLIANCE

In accordance with Rule 2520, 3.20, these modifications:

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;
2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;
4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include;
 - a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and
 - b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

In accordance with Rule 2520, the application meets the procedural requirements of section 11.4 by including;

1. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
2. The source's suggested draft permit; and
3. Certification by a responsible official that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used.

VIII. ATTACHMENTS

- A. Proposed Modified Title V Operating Permit No. S-1246-334-4, 370-5, 372-1, 373-1 and 374-1
- B. Authorities to Construct No. S-1246-334-3, 370-2, 370-3, 372-0, 373-0 and 374-0

Berry Petroleum Company
Facility # S-1246
Project # S-1124102

9/10/14

- C. Emissions Increases
- D. Application
- E. Previous Title V Operating Permits S-1246-334-2 and 370-1

ATTACHMENT A

Proposed Modified Title V Operating Permits

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-334-4

EXPIRATION DATE: 03/31/2016

SECTION: NE11 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

20,000 BBL FIXED ROOF TANK WITH VAPOR CONTROL SYSTEM, INCLUDING OPTIONAL COMPRESSOR, SHARED WITH S-1246-335, -336 AND -374, WITH VAPOR PIPING CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1246-152 (FAIRFIELD A-1 WATER PLANT)

PERMIT UNIT REQUIREMENTS

1. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC emissions from the components associated with the tank vapor recovery system shall not exceed 88.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
12. All piping, fittings, and valves on this tank, including vapor control system components, shall be inspected annually by the facility operator in accordance with EPA Method 21 with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
13. If any of the tank or vapor control system components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The permittee shall comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane): a. Eliminate the leak within 8 hours after detection; or b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and c. Eliminate the leak within 48 hours after minimization and within 56 hours of detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. If a component type for a given tank and/or tank vapor control system is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Methods used to minimize and repair leaks. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-370-4

EXPIRATION DATE: 03/31/2016

SECTION: NE 21 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

30,000 BBL TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179 ALSO SERVING TANK -372

PERMIT UNIT REQUIREMENTS

1. Total VOC emissions from the components associated with tank up to vapor control system trunk line and tank piping to vapor control system S-1246-179 shall not exceed 71.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
11. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
19. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-370-5

EXPIRATION DATE: 03/31/2016

SECTION: NE 21 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

30,000 BBL TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179 ALSO SERVING TANKS -372 AND -373

PERMIT UNIT REQUIREMENTS

1. Total VOC emissions from the components associated with tank up to vapor control system truck line and tank piping to vapor control system S-1246-179 shall not exceed 71.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
11. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
19. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-372-1

EXPIRATION DATE: 03/31/2016

EQUIPMENT DESCRIPTION:

5,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-370 (21Z LEASE)

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emissions rate, calculated using EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors and the total number of components in gas/light liquid service, shall not exceed 23.7 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
11. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
19. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-373-1

EXPIRATION DATE: 03/31/2016

EQUIPMENT DESCRIPTION:

5,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-370 (21Z LEASE)

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emissions rate, calculated using EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors and the total number of components in gas/light liquid service, shall not exceed 23.7 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
11. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
19. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
22. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
24. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-374-1

EXPIRATION DATE: 03/31/2016

EQUIPMENT DESCRIPTION:

28,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-334 (FAIRFIELD WATER PLANT)

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emissions rate, calculated using EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors and the total number of components in gas/light liquid service, shall not exceed 23.7 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
11. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT B

ATCs



AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-334-3

ISSUANCE DATE: 10/25/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY

MAILING ADDRESS: APD ACCOUNTS PAYABLE
5201 TRUXTON AVE
BAKERSFIELD, CA 93309

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE11 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

MODIFICATION OF 20,000 BBL FIXED ROOF TANK WITH VAPOR CONTROL SYSTEM, INCLUDING OPTIONAL COMPRESSOR, SHARED WITH '335 AND '336, WITH VAPOR PIPING CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1246-152, (FAIRFIELD A-1 WATER PLANT): CONNECT VAPOR RECOVERY SYSTEM TO NEW TANK S-1246-374

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emissions from the components associated with the tank vapor recovery system shall not exceed 88.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
5. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

COPY

Arnaud Marjollet, Director of Permit Services

S-1246-334-3 Sep 9 2014 4:39PM -- ROEDERS : Joint Inspection NOT Required

6. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
8. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
12. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
13. All piping, fittings, and valves on this tank, including vapor control system components, shall be inspected annually by the facility operator in accordance with EPA Method 21 with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If any of the tank or vapor control system components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The permittee shall comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane): a. Eliminate the leak within 8 hours after detection; or b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and c. Eliminate the leak within 48 hours after minimization and within 56 hours of detection. [District Rule 2201] Federally Enforceable Through Title V Permit
16. If a component type for a given tank and/or tank vapor control system is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Methods used to minimize and repair leaks. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT



AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-370-2

ISSUANCE DATE: 10/25/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY

MAILING ADDRESS: APD ACCOUNTS PAYABLE
5201 TRUXTON AVE
BAKERSFIELD, CA 93309

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE 21 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

MODIFICATION OF 30,000 BBL TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179:
CONNECT VAPOR CONTROL SYSTEM TO NEW TANK S-1246-372

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Total VOC emissions from the components associated with tank up to vapor control system truck line and tank piping to vapor control system -179 shall not exceed 71.6 lb/day. [District Rule 2201]
3. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

COPY

Arnaud Marjollet, Director of Permit Services

S-1246-370-2 Sep 9 2014 4:38PM - ROEDERS : Joint Inspection NOT Required

Southern Regional Office • 34946 Flyover Court • Bakersfield, CA 93308 • (661) 392-5500 • Fax (661) 392-5585

Printed on recycled paper.

6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
20. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
21. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
22. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
25. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit



AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-370-3

ISSUANCE DATE: 10/25/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY

MAILING ADDRESS: APD ACCOUNTS PAYABLE
5201 TRUXTON AVE
BAKERSFIELD, CA 93309

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE 21 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

MODIFICATION OF 30,000 BBL TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179:
CONNECT VAPOR CONTROL SYSTEM TO NEW TANK S-1246-373

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Total VOC emissions from the components associated with tank up to vapor control system truck line and tank piping to vapor control system -179 shall not exceed 71.6 lb/day. [District Rule 2201]
3. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

COPY

Arnaud Marjollet, Director of Permit Services

S-1246-370-3 Sep 9 2014 4:39PM -- ROEDERS : Joint Inspection NOT Required

6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
11. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
20. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
21. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
22. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
25. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit



AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-372-0

ISSUANCE DATE: 10/25/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY

MAILING ADDRESS: APD ACCOUNTS PAYABLE
5201 TRUXTON AVE
BAKERSFIELD, CA 93309

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:

UP TO 10,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-370 (21Z LEASE) (INSPECTOR TO VERIFY CAPACITY AT START-UP INSPECTION)

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Permit to Operate S-1246-209 shall be cancelled upon implementation of this Authority to Construct. [District Rule 2201]
3. Fugitive VOC emissions rate, calculated using EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors and the total number of components in gas/light liquid service, shall not exceed 23.7 lb-VOC/day. [District Rule 2201]
4. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070]
5. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
6. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

COPY

Arnaud Marjollet, Director of Permit Services

S-1246-372-0 Sep 9 2014 4:40PM -- ROEDERS : Joint Inspection NOT Required

7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623]
8. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623]
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
10. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
12. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201]
13. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201]
14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201]
15. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201]
16. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201]
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201]
18. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623]
19. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623]
20. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623]

CONDITIONS CONTINUE ON NEXT PAGE

21. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623]
22. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623]
23. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623]
24. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623]
25. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623]
26. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]



AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-373-0

ISSUANCE DATE: 10/25/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY

MAILING ADDRESS: APD ACCOUNTS PAYABLE
5201 TRUXTON AVE
BAKERSFIELD, CA 93309

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:

UP TO 10,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-370 (21Z LEASE) (INSPECTOR TO VERIFY CAPACITY AT START-UP INSPECTION)

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Permit to Operate S-1246-209 shall be cancelled upon implementation of this Authority to Construct. [District Rule 2201]
3. Fugitive VOC emissions rate, calculated using EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors and the total number of components in gas/light liquid service, shall not exceed 23.7 lb-VOC/day. [District Rule 2201]
4. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070]
5. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
6. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

COPY

Arnaud Marjollet, Director of Permit Services

S-1246-373-0 Sep 9 2014 4:40PM -- ROEDERS : Joint Inspection NOT Required

7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623]
8. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623]
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
10. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
12. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201]
13. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201]
14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201]
15. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201]
16. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201]
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201]
18. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623]
19. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623]
20. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623]

CONDITIONS CONTINUE ON NEXT PAGE

21. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623]
22. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623]
23. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623]
24. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623]
25. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623]
26. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]



AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-374-0

ISSUANCE DATE: 10/25/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY

MAILING ADDRESS: APD ACCOUNTS PAYABLE
5201 TRUXTON AVE
BAKERSFIELD, CA 93309

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:

UP TO 30,000 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR RECOVERY SYSTEM LISTED ON S-1246-334 (FAIRFIELD WATER PLANT) (INSPECTOR TO VERIFY CAPACITY AT START-UP INSPECTION)

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Permit to Operate S-1246-209 shall be cancelled upon implementation of this Authority to Construct. [District Rule 2201]
3. Fugitive VOC emissions rate, calculated using EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors and the total number of components in gas/light liquid service, shall not exceed 23.7 lb-VOC/day. [District Rule 2201]
4. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070]
5. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
6. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

COPY

Arnaud Marjollet, Director of Permit Services

S-1246-374-0 Sep 9 2014 4:40PM -- ROEDERS Joint Inspection NOT Required

7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623]
8. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623]
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
10. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
12. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201]
13. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201]
14. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201]
15. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201]
16. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201]
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201]
18. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

ATTACHMENT C

Emissions Increases

The emission increases are presented in the following table.

Emission Increases		
ATC	PTO	lb-VOC/year
S-1246-334-3	S-1246-334-4	0
S-1246-370-2	S-1246-370-4	0
S-1246-370-3	S-1246-370-5	0
S-1246-372-0	S-1246-372-1	8,651
S-1246-373-0	S-1246-373-1	8,651
S-1246-374-0	S-1246-374-1	8,651

ATTACHMENT D

Application

San Joaquin Valley Air Pollution Control District

www.valleyair.org


RECEIVED

RECEIVED
NOV 08 2012

Permit Application For: NOV 08 2012

SJVAPCD
Southern California

[] ADMINISTRATIVE AMENDMENT [X] MINOR MODIFICATION [] SIGNIFICANT MODIFICATION

1. PERMIT TO BE ISSUED TO: Berry Petroleum Company (BPC)	
2. MAILING ADDRESS: STREET/P.O. BOX: 5201 Truxtun Ave., Suite 100 CITY: Bakersfield STATE: CA 9-DIGIT ZIP CODE: 93309	
3. LOCATION WHERE THE EQUIPMENT WILL BE OPERATED: STREET: Various location in HOW CITY: _____ _____% SECTION _____ TOWNSHIP _____ RANGE _____	INSTALLATION DATE: _____
4. GENERAL NATURE OF BUSINESS: Oil and gas production	
5. DESCRIPTION OF EQUIPMENT OR MODIFICATION FOR WHICH APPLICATION IS MADE (include Permit #'s if known, and use additional sheets if necessary) Implement six Authorities to Construct for five tanks S-1246-334-3, -370-2, -370-3, -372-0, -373-0, and -374-0.	
6. TYPE OR PRINT NAME OF APPLICANT: John Ludwick	TITLE OF APPLICANT: Regulatory Compliance Specialist
7. SIGNATURE OF APPLICANT: 	DATE: 11/8/2012 PHONE: (661) 616-3807 FAX: (661) 616-3892 EMAIL: jjl@bry.com

For APCD Use Only:

DATE STAMP	FILING FEE RECEIVED: \$ _____ CHECK#: _____
	DATE PAID: _____
	PROJECT NO: S-1124102 FACILITY ID: S-1246

Title V - Minor Mod

**San Joaquin Valley
Unified Air Pollution Control District**

TITLE V MODIFICATION - COMPLIANCE CERTIFICATION FORM

I. TYPE OF PERMIT ACTION (Check appropriate box)

☐ SIGNIFICANT PERMIT MODIFICATION
☒ MINOR PERMIT MODIFICATION

☐ ADMINISTRATIVE
AMENDMENT

COMPANY NAME: Berry Petroleum Company (BPC)	FACILITY ID: S-1246
1. Type of Organization: <input checked="" type="checkbox"/> Corporation <input type="checkbox"/> Sole Ownership <input type="checkbox"/> Government <input type="checkbox"/> Partnership <input type="checkbox"/> Utility	
2. Owner's Name: Berry Petroleum Company (BPC)	
3. Agent to the Owner: Tim Crawford	

II. COMPLIANCE CERTIFICATION (Read each statement carefully and initial all circles for confirmation):

- ☒ Based on information and belief formed after reasonable inquiry, the equipment identified in this application will continue to comply with the applicable federal requirement(s).
- ☒ Based on information and belief formed after reasonable inquiry, the equipment identified in this application will comply with applicable federal requirement(s) that will become effective during the permit term, on a timely basis.
- ☒ Corrected information will be provided to the District when I become aware that incorrect or incomplete information has been submitted.
- ☒ Based on information and belief formed after reasonable inquiry, information and statements in the submitted application package, including all accompanying reports, and required certifications are true accurate and complete.

I declare, under penalty of perjury under the laws of the state of California, that the forgoing is correct and true:



Signature of Responsible Official

11/7/2012

Date

Robert Boston

Name of Responsible Official (please print)

Manager of EHS

Title of Responsible Official (please print)

ATTACHMENT E

Previous Title V Operating Permits

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-334-2

EXPIRATION DATE: 03/31/2016

SECTION: NE11 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

20,000 BBL FIXED ROOF TANK WITH VAPOR CONTROL SYSTEM, INCLUDING OPTIONAL COMPRESSOR, SHARED WITH '335 AND '336, WITH VAPOR PIPING CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1246-152, (FAIRFIELD A-1 WATER PLANT)

PERMIT UNIT REQUIREMENTS

1. The overall efficiency of the tank vapor collection and control system shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC emissions from the components associated with the tank vapor recovery system shall not exceed 88.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
12. All piping, fittings, and valves on this tank, including vapor control system components, shall be inspected annually by the facility operator in accordance with EPA Method 21 with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
13. If any of the tank or vapor control system components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The permittee shall comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane): a. Eliminate the leak within 8 hours after detection; or b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and c. Eliminate the leak within 48 hours after minimization and within 56 hours of detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. If a component type for a given tank and/or tank vapor control system is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Methods used to minimize and repair leaks. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-370-1

EXPIRATION DATE: 03/31/2016

SECTION: NE 21 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:

28,000 BBL FIXED-ROOF CRUDE OIL STORAGE TANK CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1246-179

PERMIT UNIT REQUIREMENTS

1. VOC emissions from the components associated with tank up to vapor control system truck line shall not exceed 12.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC emissions from the components associated with tank piping to vapor control system '179 shall not exceed 58.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit an accurate fugitive component count and the resulting emissions calculated pursuant to EPA document, "EPA Protocol for Equipment Leak Emission Estimate," Table 2-4, "Oil and Gas Production Operations," using average emission factors. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BERRY PETROLEUM COMPANY

Location: HEAVY OIL WESTERN STATIONARY SOURCE, KERN COUNTY, CA

S-1246-370-1 : Sep 9 2014 4:40PM -- ROEDERS

11. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Comply with the following requirements to repair leaking components that have a gas leak >10,000 ppmv (measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane):
 - a. Eliminate the leak within 8 hours after detection; or
 - b. If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and
 - c. Eliminate the leak within 48 hours after minimization; and
 - d. In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit
20. This tank shall be degassed before commencing interior cleaning by a degassing method in Section 5.7.5.4.1 through 5.7.5.4.4 of District Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
21. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
22. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.